

Via Pentima Bassa, 21 Terni 05100 TR phone/fax: +39.0744.49.29.13

INFN ROMA - CARSO

ENVIRONMENTAL TEST REPORT

doc: STAR TRACKER_THERMAL VACUUM CYCLING TEST date: 06/07/06

rev: A01 pag: 1 /17

file: ENVRPT_ST-06JULY2K6

EN1	/IRO	NMEN	TAL	TEST	REPO	RT

ENVRPT_ST-06JULY2K6 date: July 06, 2006

signature

test report prepared by:	06/07/06	Ing. S. Borsini	Serous Borsin
		Test Engineer and Responsible	
test report controlled by:			
approved by:			

change record

date	change description	revision	
06/07/2006	first issue	A01	



Via Pentima Bassa, 21 Terni 05100 TR phone/fax: +39.0744.49.29.13

INFN ROMA - CARSO

ENVIRONMENTAL TEST REPORT

doc: STAR
TRACKER_THERMAL
VACUUM CYCLING TEST

date: 06/07/06 rev: A01

pag: 2/17

file: ENVRPT_ST-06JULY2K6

NOTICE

Reproduction or duplication of any portion of this report is expressively forbidden, except by those contractors receiving it directly from authorized data interchange offices or the originator, for their internal use or the use of they subcontractors. Reproduction or display of all or any portion of this material for any sales, advertising or publicity purposes is prohibited.

TEST REPORT DESCRIPTION

REPRODUCTION OF THIS REPORT

This document is generated by the S.E.R.M.S. Laboratory and reports on the setup, the operation and the results of the test performed on the customer Device Under Test (D.U.T.); several sections compose this report: all of them have been integrated and adapted to the specific tests performed on the D.U.T.



Via Pentima Bassa, 21 Terni 05100 TR phone/fax: +39.0744.49.29.13

ENVIRONMENTAL TEST REPORT

doc: STAR TRACKER_THERMAL VACUUM CYCLING TEST date: 06/07/06

rev: A01 pag: 3 /17

file: ENVRPT_ST-06JULY2K6

INFN ROMA - CARSO

CONTENTS

GENERAL INFORMATION	4
APPLICABLE LAWS AND RULESSERMS FACILITY - QUALITY ASSURANCE INFORTEST SUMMARY	5 MATION 6 8
TEST RESULTS	9
REMARKS	9
TEST DIARY	10
TEST SET-UP <i>UNPACKAGE AND POSITIONING</i> <i>THERMAL SENSORS POSITIONING ON THE DUT</i>	
TEST GRAPHS	16
LIST OF THE ANNEX	ERRORE. IL SEGNALIBRO NON È DEFINITO.



Via Pentima Bassa, 21 Terni 05100 TR phone/fax: +39.0744.49.29.13

ENVIRONMENTAL TEST REPORT

doc: STAR
TRACKER_THERMAL
VACUUM CYCLING TEST

date: 06/07/06 rev: A01

pag: 4 /17

file: ENVRPT_ST-06JULY2K6

INFN ROMA - CARSO

GENERAL INFORMATION

Job Number:

Test performed on:

Amica Star Tracker (AST) electronics - QM Model

Contractor:

INFN Roma - CARSO Trieste

Contractor responsible:

P.Trampus (CARSO Trieste) C.Gargiulo (INFN-Roma)

Test responsible:

Three different subjects - CARSO, INFN-Roma and S.E.R.M.S.- have participated to this test. The applicable procedure has been written by INFN-Roma (C.Gargiulo) **Document No.**AMS_02_AST_050106_rev1.

Roles and responsibilities of the participating subjects are defined as follow:

- Test conduction has been responsibility of INFN-Roma. INFN-Roma personnel units at SERMS have contributed to the setup and disassembly phases, verifying thermal sensor locations and failure. They have the responsibility to issue procedure variation sheet (PVS).
- AST electronics switch-on/switch-off operations, monitoring and functional tests have been performed by CARSO personnel units. Recorded data from AST electronics functional test are under responsibility of CARSO.
- SERMS has been responsible for the test facility and the measurement hardware (thermal vacuum chamber, thermal sensors, pressure sensors, data acquisition chain).
- SERMS has been responsible of the environmental parameters and AST electronics temperature measurements along the whole test. Recorded data have been handled only by SERMS gualified personnel. They regularly monitored the test execution.

The SERMS project manager responsible for the test has been Ing. Serena Borsini.



Via Pentima Bassa, 21 Terni 05100 TR phone/fax: +39.0744.49.29.13 ENVIRONMENTAL TEST REPORT

doc: STAR TRACKER_THERMAL VACUUM CYCLING TEST date: 06/07/06

rev: A01 pag: 5 /17

file: ENVRPT_ST-06JULY2K6

INFN ROMA - CARSO

APPLICABLE LAWS AND RULES

CUSTOMER TEST PROCEDURE

AMS_02 STAR TRACKER - THERMAL BALANCE / THERMAL VACUUM TEST PLAN Document No. AMS_02_AST_050106_rev1, 21/02/06 and subsequent PVSs

S.E.R.M.S Lab. - INTERNAL TEST PROCEDURE 09-PT-TVM-A01-26APR2K6.doc THERMOVACUUM TEST PROCEDURE

D.L. 19 settembre 1994, n.626

Attuazione delle direttive 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE e 90/679/CEE riguardanti il miglioramento della sicurezza e della salute dei lavoratori sul luogo di lavoro, e successive modifiche;

MIL-HDBK-831 23 April 1999

Preparation of Test Reports (guidance only);

UNI -10653 - November 1997

Quality product technical documentation (guidance only);

UNI CEI EN45001

general criterion for test laboratory operation;

UNI CEI 70001

norm certificate test laboratory terms and definitions;

UNI CEI 70011

guide for test result presentation;



05100 TR

ENVIRONMENTAL TEST REPORT

doc: : STAR TRACKER_THERMAL VACUUM CYCLING TEST

date: 06/07/06

rev: A01 pag: 6 /17

file: ENVRPT_ST-06JULY2K6

phone/fax: +39.0744.49.29.13

INFN ROMA - CARSO

SERMS FACILITY - QUALITY ASSURANCE INFORMATION

EQUIPMENT	MANUFACTU RER	P/N	S/N	ACCURACY	NEXT CAL DATE	REMARKS
TV chamber with pressure measurement and temperature acquisition system	Angelantoni	HVT-2000 MC	10107	NA	certificate (first installation) is	Detailed technical informations can be provided by the Facility.
THERMAL RIBBONS	MINCO	S651		Class B tolerance	13/11/ 2006	None
Pressure sensor	LEYBOLD	ITR090 – No.12090	Part number: 2809	±15% for reading in the range of 1 x 10 ⁻⁸ 1 x 10 ⁻² mbar after 5 min. os stabilization	13/11/ 2006	None
THERMAL SENSOR – thin film elements	MINCO	S651PD	NA	100Ω ±0,12 %	28/02/2007	None



degli Effetti delle Radiazioni sui Materiali per lo Spazio

Via Pentima Bassa, 21 Terni 05100 TR phone/fax: +39.0744.49.29.13

ENVIRONMENTAL TEST REPORT

doc: : STAR TRACKER THERMAL VACUUM CYCLING TEST

date: 06/07/06

rev: A01 pag: 7 /17

file: ENVRPT_ST-06JULY2K6

EQUIPMENT	MANUFACTU RER	P/N	S/N	ACCURACY	NEXT CAL DATE	REMARKS
DAQ	NATIONAL INSTRUMEN TS	6036E	11DAA16	INPUT 16 bit 200kS/sec ±0,05 to ± 10 V	6/04/2007	none
Feed troughs plugs	POSITRONIC S			NA	10/01/2007	Visual inspection
Flat Cable	RS			NA	15/03/2007	Visual inspection



Via Pentima Bassa, 21 Terni 05100 TR phone/fax: +39.0744.49.29.13

INFN ROMA - CARSO

ENVIRONMENTAL TEST REPORT

doc: STAR TRACKER_THERMAL VACUUM CYCLING TEST

date: 06/07/06 rev: A01 pag: 8 /17 file: ENVRPT_ST-06JULY2K6

TEST SUMMARY

The actual procedure adopted in the test is schematically presented in Figure 1. Eight intermediate cycles have been executed.




FIGURE 1 – TEST TEMPERATURE PROFILE

The cycle temperature values are listed in the following table; the intermediate cycles are eight.

	HOT	COLD
Non-operation	85°C	-45°C
Operation	60°C	-35°C
Best-Performance	40°C	-25°C

It derives from the approved reference profile on the customer procedure: Document No. AMS_02_AST_050106_rev1, 21/02/06 and the related PVS approved by the AMS Thermal Working Group.

Due to the duration of the test, the full set of recorded data has been splitted for data handling purposes in sub-phases: the depressurization phase (chamber evacuation), 8 sub-phases (each corresponding to a temperature cycle) and the Return to Ambient phase.



Laboratorio per lo Studio degli Effetti delle Radiazioni sui Materiali per lo Spazio Via Pentima Bassa, 21 Terni

05100 TR phone/fax: +39.0744.49.29.13

ENVIRONMENTAL TEST REPORT

doc: STAR TRACKER_THERMAL VACUUM CYCLING TEST

date: 06/07/06 rev: A01 pag: 9 /17 file: ENVRPT_ST-

06JULY2K6

INFN ROMA - CARSO

TEST RESULTS

The AST electronics qualification model has been tested at S.E.R.M.S. in the Thermal Vacuum Chamber (TVC) during the period March 14^{th} – March 23^{th} 2006.

The test has been performed according to the test profile shown in the previous section of this report. CARSO experts have attended the test and operated the AST electronics during the switch-on/switch-off and functional test phases.

No malfunctioning has been observed in the S.E.R.M.S equipment: the environmental parameters in the TVC matched the customer requests and were continuously recorded.

The AST electronics temperatures have been continuously monitored in 5 locations and their values recorded during the whole test period. The complete set of recorded data can be provided on customer request. In this report will be summarized only the most significant test data.

All the commitments of S.E.R.M.S. with the customer have been fulfilled and the test can be declared successfully completed for what concerns the items under S.E.R.M.S. responsibility.

The complete step-by-step procedure followed and wrote during the test is attached as annex to this report.

REMARKS

REMARK #1

Initially the stabilization criteria that should be used was the same of AMS_02 EHV and RHV Bricks Thermal Test Specification: when $\Delta T/\Delta t \le 1^{\circ}$ C/hr is reached and maintained at least for 1 hour, then the T shall stabilize for at least 2 hours.

During the test this criteria has been modified: when $\Delta T/\Delta t \le 1^{\circ}C/hr$ (evaluated on a period of ten minutes) is reached then the T shall stabilize for at least 2 hours.

Regarding this procedure change a PVS has been issued and reported as Annex to this report.

REMARK# 2

During the first phase of the test (Hot phase of the first cycle) only the cold plate temperature control has been enabled. Before the hot stabilization phase of the first cycle also the shroud temperature control has been enabled in order to obtain on the DUT the temperature values required by the test procedure.



Via Pentima Bassa, 21 Terni 05100 TR phone/fax: +39.0744.49.29.13

INFN ROMA - CARSO

ENVIRONMENTAL TEST REPORT

doc: STAR TRACKER_THERMAL VACUUM CYCLING TEST

date: 06/07/06 rev: A01 pag: 10 /17 file: ENVRPT_ST-

06JULY2K6

TEST DIARY

DUT incoming: march 10, 2006; Test Set-Up: march 14, 2006;

TVC test: march 14, 2006 – march 23, 2006.

Disassembly: march 24, 2006.

TEST SET-UP

The Amica Star Tracker electronics was tested in the Thermo Vacuum Chamber fixed to the lower cold plate by the thermal vacuum cycling test fixture made of Aluminium alloy. CCD (Charged Coupled Device) was oriented in order to point to a light spot used for functional test.

During the set up phase the main activities performed have been:

- unpackage and cleaning of the electronic board, the Aluminium fixture and the screws needed to place the fixture on cold plate and to fix the electronic board on it.
- thermal sensors positioning in the TVC
- thermal sensors positioning on the electronics

UNPACKAGE AND POSITIONING




FIGURE 2 – TEST SET-UP OF THE AST ELECTRONICS (PC BOARD AND CCD)



Via Pentima Bassa, 21 Terni 05100 TR phone/fax: +39.0744.49.29.13

INFN ROMA - CARSO

ENVIRONMENTAL TEST REPORT

doc: STAR TRACKER_THERMAL VACUUM CYCLING TEST

date: 06/07/06 rev: A01 pag: 11 /17 file: ENVRPT_ST-06JULY2K6




FIGURE 3 - HARDWARE POSITIONING ON THE AL FIXTURE.




FIGURE 4 – AST POSITIONING INSIDE THE THERMO-VACUUM CHAMBER ON THE LOWER COLD PLATE.

The Aluminium alloy fixture reproduce the same I/F condition that are in the flight configuration; in order to have a good thermal connection between the fixture and the cold plate, a layer of thermal conductive material (Cho-Term) was placed between the fixture and plate.



Via Pentima Bassa, 21 Terni 05100 TR phone/fax: +39.0744.49.29.13

INFN ROMA - CARSO

ENVIRONMENTAL TEST REPORT

doc: STAR TRACKER_THERMAL VACUUM CYCLING TEST

date: 06/07/06 rev: A01 pag: 12 /17 file: ENVRPT_ST-06JULY2K6




FIGURE 5 - DETAIL OF CHO-TERM LAYER PLACED BETWEEN THE AL FIXTURE AND THE COLD PLATE.

THERMAL SENSORS POSITIONING ON THE DUT

A total of 5 Thermal Sensors (PT100 sensors) have been installed on the AST electronics by S.E.R.M.S. personnel under the direction of INFN-Roma and CARSO personnel. Four sensors to monitor the temperature of the electronics in different points during the test. One sensor was installed on the AL fixture to drive the cold plate and shroud temperature during the test (CTS-Control Temperature Sensor).




FIGURE 6 – TEMPERATURE SENSORS POSITIONING ON THE DUT.



Via Pentima Bassa, 21 Terni 05100 TR phone/fax: +39.0744.49.29.13 TEST REPORT

doc: STAR TRACKER_THERMAL VACUUM CYCLING TEST

date: 06/07/06 rev: A01 pag: 13 /17 file: ENVRPT_ST-06JULY2K6

INFN ROMA - CARSO

The temperature sensors are installed as specified in the next table:

Sensor number	Location	Position	
1	ASTCE Electronic board 3	On ACTEL fpga	
2	ASTCE Electronic board 3	On Copper strip on PCB Board	
3	ASTCD ccd board 2	On PCB Board	
4	ASTCC ccd board 1	On Copper plate	

ENVIRONMENTAL

The sensors used are the chamber sensors and they are installed using Kapton tape. After positioning, all sensors have been tested to verify possible failures after installation .

In the following are presented the photographs of all sensors after positioning.




FIGURE 7 – PT100 N°1 AND 2 POSITIONING.



Via Pentima Bassa, 21 Terni 05100 TR phone/fax: +39.0744.49.29.13

INFN ROMA - CARSO

ENVIRONMENTAL TEST REPORT

doc: STAR TRACKER_THERMAL VACUUM CYCLING TEST

date: 06/07/06 rev: A01 pag: 14 /17 file: ENVRPT_ST-

06JULY2K6




FIGURE 8 – PT100 N° 3 POSITIONING.




FIGURE 9 – PT100 N° 4 POSITIONING.



Via Pentima Bassa, 21 Terni 05100 TR phone/fax: +39.0744.49.29.13

INFN ROMA - CARSO

ENVIRONMENTAL TEST REPORT

doc: STAR TRACKER_THERMAL VACUUM CYCLING TEST

date: 06/07/06 rev: A01 pag: 15 /17 file: ENVRPT_ST-06JULY2K6




FIGURE 10 - CONTROL TEMPERATURE SENSOR POSITIONING.

CTS



Via Pentima Bassa, 21 Terni 05100 TR phone/fax: +39.0744.49.29.13

INFN ROMA - CARSO

ENVIRONMENTAL TEST REPORT

doc: STAR TRACKER_THERMAL VACUUM CYCLING TEST

date: 06/07/06 rev: A01 pag: 16 /17 file: ENVRPT_ST-06JULY2K6

TEST GRAPHS

All the control and environmental parameters in the TVC have been continuously monitored and recorded during the test. The AST electronics temperatures have been continuously monitored in 5 locations and their values recorded during the whole test period.

In this section, the graphs summarizing the temporal evolution of all measured quantities during the whole test period are reported.

A more detailed set of graphs has been also produced for the evacuation phase and the test subphases as defined beforehand in the test summary section. These graphs have been reported in Chamber evacuation, in Annex 01 to Annex 08 and Post Eight phase annex to this report.

Hereby the S.E.R.M.S. guarantees that:

- the handling of the test data has been done only by qualified members of the S.E.R.M.S staff.
- all graphs presented in this report and its annex are a truthful representation of the recorded data and have been solely produced by the S.E.R.M.S. engineer in charge of the test.

The complete set of recorded data can be provided on customer request.

More detailed graphs relative to specific measurements can be produced on customer request.



Via Pentima Bassa, 21 Terni

ENVIRONMENTAL TEST REPORT

doc: STAR TRACKER_THERMAL VACUUM CYCLING TEST

date: 06/07/06

rev: A01 pag: 17 /17

file: ENVRPT ST-06JULY2K6

05100 TR phone/fax: +39.0744.49.29.13




FIGURE 11 – PRESSURE PROFILE OF THE TEST. THE PEAKS CORRESPOND TO THE HOT PHASE OF EACH CYCLE.



degli Effetti delle Radiazioni sui Materiali per lo Spazio

Via Pentima Bassa, 21 Terni 05100 TR phone/fax: +39.0744.49.29.13


ENVIRONMENTAL TEST REPORT

doc: STAR TRACKER THERMAL VACUUM CYCLING TEST

date: 06/07/06

rev: A01 pag: 18 /18

file: ENVRPT ST-06JULY2K6





degli Effetti delle Radiazioni sui Materiali per lo Spazio Via Pentima Bassa, 21 Terni

05100 TR phone/fax: +39.0744.49.29.13


ENVIRONMENTAL TEST REPORT

doc: STAR TRACKER_THERMAL VACUUM CYCLING TEST

date: 06/07/06 rev: A01

pag: 19 /19

file: ENVRPT ST-06JULY2K6





Laboratorio per lo Studio degli Effetti delle Radiazioni sui Materiali per lo Spazio Via Pentima Bassa, 21 Terni

05100 TR

phone/fax: +39.0744.49.29.13

ENVIRONMENTAL TEST REPORT

doc: STAR TRACKER THERMAL VACUUM CYCLING

TEST date: 06/07/06

rev: A01 pag: 20 /20

file: ENVRPT_ST-06JULY2K6

INFN ROMA - CARSO

ANNEX LIST

- CHAMBER EVACUATION
- ANNEX 01- FIRST CYCLE
- ANNEX 02- SECOND CYCLE
- ANNEX 03 THIRD CYCLE
- ANNEX 04 FOURTH CYCLE
- ANNEX 05 FIFTH CYCLE
- ANNEX 06 SIXTH CYCLE
- ANNEX 07 SEVENTH CYCLE
- ANNEX 08 EIGHTH CYCLE
- POST EIHGTH ANNEX- RETURN TO AMBIENT CONDITIONS PHASE
- PROCEDURE VARIATION SHEETS
- STEP BY STEP PROCEDURE

END (OF.	DO	CUN	IENT
-------	-----	----	-----	------